

27Mt 30/70 Shipper Bitutainer™ Model TR-T-278 (For Direct Fire Heating)



Suitable for Storage and Transportation of Bitumen, Bitumen Emulsions, PMBs and Heavy Fuel Oils

A unique concept in Bitumen Distribution with 30% more carrying capacity than Conventional Tank Containers

- Nominal Capacity 29,000 Litres
- ISO 1496 Part 3 - Type 70 Classification
- High Performance factory fitted heating tubes
- Improved Valve Box Design = Reduced Heat Loss
- Valve Box Cover & Chimneys secured with chains for security & increased ease of use for operators when the Bitutainer is mounted on a trailer or rail car
- Robust and Durable Design makes this Bitutainer™ ideal for operation in harsh working environments
- High Value Factory Installed Insulation and Pressed Corten Steel Outer Skin
- Fully Framed with Corner Twist Locks and Damage Reinforcement Plates
- Transported as a Standard 20ft ISO Tank Container with Lloyds Approval
- Range of bitumen handling equipment available including pumps and hoses



Heating equipment required:

- Quick Fit Diesel Burners Set
- Stainless Steel Flame Liners

Ratings:

Max GW 35,125 Kgs
Payload 28,825 Kgs
Tare Wt. <6,300 Kgs

Measures:

Length 6,058 mm (20')
Width 2,438 mm (8')
Height 2,591 mm (8'6")